



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification<sup>6</sup> :</b> <b>H04Q 7/38, 7/22</b>	<b>A2</b>	<b>(11) International Publication Number:</b> <b>WO 98/27777</b> <b>(43) International Publication Date:</b> 25 June 1998 (25.06.98)
<b>(21) International Application Number:</b> PCT/IB97/01579 <b>(22) International Filing Date:</b> 17 December 1997 (17.12.97) <b>(30) Priority Data:</b> 08/769,650 19 December 1996 (19.12.96) US <b>(71) Applicant (for all designated States except US):</b> NORTHERN TELECOM LIMITED [CA/CA]; World Trade Center of Montreal, 8th floor, 380 St. Antoine Street West, Montreal, Quebec H2Y 3Y4 (CA). <b>(72) Inventors; and</b> <b>(75) Inventors/Applicants (for US only):</b> CURTIS, David, E. [US/US]; 1550 Evergreen Drive, Allen, TX 75002 (US); BOOK, William, B. [US/US]; 1012 Winslow, Allen, TX 75002 (US); BOETTGER, David, A. [US/US]; 2111 E. Beltline Road #156A, Richardson, TX 75091 (US); JALALI, Ahmad [US/US]; 7424 Wildflower Drive, Plano, TX 75024 (US). <b>(74) Agents:</b> MCCOMBS, David et al.; Haynes and Boone, L.L.P., Suite 3100, 901 Main Street, Dallas, TX 75202-3789 (US).		<b>(81) Designated States:</b> AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). <b>Published</b> <i>Without international search report and to be republished upon receipt of that report.</i>
<b>(54) Title:</b> RADIO LINK QUALITY HANDOFF TRIGGER		
<b>(57) Abstract</b>		
<p>A method and system is disclosed for triggering handoff of a call from a CDMA network to an AMPS network on which it is overlaid responsive to a determination that the CDMA RF link has degraded to such an extent that the call quality will be degraded significantly or the call is likely to be dropped is disclosed. A handoff of a call from a CDMA network to an AMPS network if, at a given time: (1) the number of forward link erasures is greater than a first maximum number of forward link erasures; or (2) the number of reverse link erasures is greater than a first maximum number of forward link erasures; or (3) the number of forward link erasures is greater than a second maximum number of forward link erasures and the forward traffic channel gain is greater than a maximum forward traffic channel gain; or (4) the number of reverse link erasures is greater than a second maximum number of reverse link erasures and the ratio of energy per bit to noise power spectral density on the reverse link ("EB/NO") is greater than a maximum EB/NO. In alternative embodiments, the present invention may be used to trigger handoff of a call from a first CDMA cell site to a second CDMA cell site or to an AMPS cell site serving a cell on which the cell served by the first CDMA cell site is not overlaid.</p>		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroun	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## **RADIO LINK QUALITY HANDOFF TRIGGER**

### **Technical Field**

The invention relates generally to cellular telephone systems and, more particularly, to a method of triggering a handoff of a call from a cell site in a first cellular telephone network, such as a code division multiple access ("CDMA") network, to a cell site in a second cellular telephone network, such as an advanced mobile phone service ("AMPS") network.

### **Background of the Invention**

In cellular telephone systems, the served area is divided into cells, each of which may be further divided into sectors. Each cell is served by a single base station, or cell site, and each base station is connected to a message switching center ("MSC") via appropriate hardware links. A mobile unit is connected to the MSC by establishing a radio frequency ("RF") link with a nearby cell site.

Currently, there are several different types of cellular access technologies for implementing a cellular telephone network, including, for example, code division multiple access, or "CDMA", and advanced mobile phone service, or "AMPS". In a CDMA network, a single radio frequency is used simultaneously by many mobile units and each mobile unit is assigned a "code" for deciphering its particular traffic on that frequency. In contrast, in an AMPS network, each mobile unit is assigned a different radio frequency on which to communicate.

Referring to Figures 1A-1D, it will be recognized that, as shown in Figure 1A, in order for a mobile unit, such as the mobile unit 10, to communicate in a cellular telephone network, designated generally by a reference numeral 12, two links must be established, including an RF link 14 between the mobile unit 10 and a first cell site, such as a cell site A, and a hardware link 16 between the cell site and a mobile switching center ("MSC") 18. As shown in Figure 1B, as the mobile unit 10 moves away from the cell site A, the RF link 14 will eventually become too weak to support

communications between the cell site A and the mobile unit 10 and will eventually disconnect, resulting in the call in progress being dropped. Clearly, this is not acceptable. Accordingly, as illustrated in Figures 1C and 1D, to avoid this result, as the mobile unit 10 nears a second cell site, in this case, a cell site B, a new communications path between the mobile unit 10 and the MSC 18, comprising an RF link 20 and a hardware link 22 between the cell site B and the MSC 18, is established. At this point, the mobile unit 10 is directed to end communication with the cell site A and begin communication with the cell site B.

Although as shown in Figures 1A-1D, the cell sites are connected by a single MSC 18, it will be recognized that cell sites may be connected by more than one MSC connected to one another via appropriate links. Moreover, the cell sites A and B may be located in two separate cellular telephone networks, such as a CDMA and an AMPS network, respectively, or in two different CDMA networks.

The situation in which a mobile unit ends communication with one cell site and begins communication with a second cell site, is referred to as a "handoff". The specific example illustrated in Figures 1A-1D is referred to as a "hard handoff", because the link between the mobile unit 10 and the MSC 18 via the cell site A is broken before the link between the mobile unit and the MSC via the cell site B is established.

In many cases, an AMPS cellular network already exists in an area in which a CDMA network is to be installed, in which case the CDMA network will often be overlaid on top of the AMPS network. In such cases, it is conceivable that there will be situations in which it would be advantageous to effect the handoff of a call from a CDMA cell site to an AMPS cell site. For example, it is possible that there will be areas that are covered by the AMPS network that are not covered by the CDMA network, due to different propagation characteristics of the two technologies, slight differences in the location of the various cell sites, and holes, or nulls, in the CDMA network

coverage due to topography and cell site planning. Such coverage holes in the CDMA network can degrade call quality and, at worst, result in dropped calls. In addition, many cellular service providers have existing in-building and/or underground AMPS network coverage. The RF propagation characteristics of an 800 MHz signal in an AMPS network may be able to penetrate such structures better than a 1900 MHz signal in a CDMA network; therefore, a call maintained by the CDMA network could lose quality or be dropped. Finally, because large urban areas are typically converted to CDMA before rural areas, the major highways between such areas will also be converted to CDMA, to provide seamless coverage for travelers between such areas. However, as a mobile unit exits the highway, it also exits CDMA coverage area, eventually resulting in a call-in-progress being dropped.

In the foregoing situations, it would be beneficial to handoff a call from a CDMA network to an AMPS network on which it is overlaid once the call has degraded to a point at which it appears that the call will eventually be dropped.

It will be appreciated that CDMA network service providers would like to maintain a call within the CDMA network rather than hand it off to an AMPS network, as handing off a call too soon results in lost revenue for the CDMA network service provider; however, waiting too long to do so will likely result in a decrease in call quality and an increase in dropped calls, both of which result in an increase in customer complaints.

Therefore, what is needed is a method of triggering handoff of a call from a CDMA cell site to a second cell site, such as an AMPS cell site, responsive to a determination that the RF link between the mobile unit and the CDMA cell site has degraded to such an extent that a disconnection of the link is imminent.

### Summary of the Invention

The present invention, accordingly, provides a method and system for triggering handoff of a call from a CDMA network to an AMPS network on which it is overlaid responsive to a determination that the CDMA RF link  
 5 has degraded to such an extent that the call quality will be degraded significantly or the call is likely to be dropped. A handoff of a call from a CDMA network to an AMPS network is triggered by one of the following four conditions being met:

$$(1) \quad FER_{\text{forward}}(t) > FER_{\text{max forward}}$$

$$10 \quad (2) \quad FER_{\text{reverse}}(t) > FER_{\text{max reverse}}$$

$$(3) \quad FER_{\text{forward}}(t) > FER_{\text{max forward}_2} \text{ and } TCG(t) > TCG_{\text{max}}$$

$$(4) \quad FER_{\text{reverse}}(t) > FER_{\text{max reverse}_2} \text{ and } EBNO(t) > EBNO_{\text{max}}$$

where  $FER_{\text{forward}}(t)$  represents a measure of the quality of the forward link over a given window of time,  $FER_{\text{reverse}}(t)$  is a measure of the quality of the  
 15 reverse link over a given window of time,  $TCG(t)$  is a measure of the power being sent to the mobile unit on the forward link over a given window of time, and  $EBNO(t)$  is a ratio of energy per bit to noise power spectral density used in power control to ensure that the reverse link meets the target frame error rate over a given window of time.

20 In alternative embodiments, the handoff trigger described herein may be used to trigger handoff of a call from a first CDMA cell site serving a first CDMA cell to a second CDMA cell site serving a second CDMA cell or to an AMPS or other cell site serving an AMPS cell on which said first CDMA cell is not overlaid.

A technical advantage achieved is that, in a CDMA network that is overlaid on an AMPS network, CDMA calls that would otherwise be severely degraded or dropped due to a poor CDMA RF link can be handed off to AMPS instead.

5 Another technical advantage achieved with the invention is that it optimizes the time at which a call is handed off from a first cell site to a second cell site.

Yet another technical advantage achieved with the invention is that it enables a call to be handed off to another cell site as soon as the RF link  
10 between the mobile unit and a CDMA cell site has degraded to such an extent that the quality of the call has been degraded beyond an acceptable level or the call is likely to be dropped.

#### **Brief Description of the Drawings**

Figures 1A-1D illustrate hard handoff of a call from one cell site to  
15 another.

Figures 2A-2C illustrate hard handoff of a call from a CDMA cell site to an AMPS cell site in accordance with the teaching of the present invention.

Figure 3 is a flowchart of the operation of the present invention for  
20 triggering handoff of a call from a CDMA cell site to an AMPS cell site.

#### **Description of the Preferred Embodiment**

Figures 1A-1D illustrate hard handoff of a call from one cell site to another, as described in detail above.

Referring now to Figures 2A-2C, hard handoff of a call from a CDMA  
25 cell site to an AMPS cell site in accordance with the features of the present invention will be shown and described. In particular, a CDMA cell 204 serviced by a CDMA cell site 206 is overlaid on an AMPS cell 200 serviced by an AMPS cell site 202. It will be recognized that although the CDMA cell 204 is shown as covering the entire geographical area covered by the AMPS  
30 cell 200, this will not necessarily be the case. On the contrary, it is possible

that only portions of the areas covered by the cells 200, 204, will be the same or that the AMPS cell 200 will cover a greater area than the CDMA cell 204. In addition, it will also be recognized that areas covered by the cells 200, 204, will most likely not be round, as represented in the drawings.

5 Moreover, it will be recognized that the cells 200, 204, are not necessarily the same size, i.e., one may cover a greater area than the other. Accordingly, the term "overlaid" will be used to encompass any of these situations in which a CDMA cell, such as the cell 204, covers at least some of the same geographical area as covered by an AMPS cell, such as the cell 200.

10 As shown in Figure 2A, a mobile unit 208 is in communication with an MSC 210 via an RF link 212 between the mobile unit and the CDMA cell site 206 and a hardware link 214 between the CDMA cell site and the MSC. Referring to Figures 2B and 2C, as the mobile unit 208 continues to move in a direction indicated by an arrow Z, an obstruction 216 begins to interfere  
15 with the RF link 212 between the mobile unit and the CDMA cell site 206. Accordingly, as will be described in detail below, once the call quality has degraded to a point at which it is likely that the call will eventually be dropped, the links 212 and 214 are terminated and an RF link 218 between the AMPS cell site 202 and the mobile unit 208 is established, such that the  
20 mobile unit is in communication with the MSC 210 via the RF link 218 and a hardware link 220 between the AMPS cell site and the MSC.

Although cell sites are shown in Figures 2A-2C as being connected by a single MSC 210, it will be recognized that cell sites may be connected by more than one MSC connected to one another via appropriate links.

25 A good handoff trigger must correctly identify an upcoming call drop a high percentage of the time. Such detection must be accomplished sufficiently early so that the quality of the forward link is good enough for the mobile unit to receive the handoff message with a high degree of certainty. Another trigger characteristic is that the triggering algorithm  
30 should not be too sensitive, or it will falsely trigger too often, causing

unnecessary handoffs to the AMPS network and unnecessary CDMA/AMPS messaging.

The following have been identified as good indicators of RF link quality; therefore, by monitoring their values, one can determine when the  
 5 CDMA call is in RF trouble:

**Forward Link Erasures ("FER<sub>forward</sub>")**, which is a measure of the quality of the forward link. An erasure is equivalent to one bad frame of data.

**Reverse Link Erasures ("FER<sub>reverse</sub>")**, which is a measure of the  
 10 quality of the reverse link. An erasure is equivalent to one bad frame of data.

**Forward Traffic Channel Gain ("TCG")**, which is a measure of the power being sent to the mobile unit on the forward link.

**Reverse EB/NO ("EBNO")**, which is a ratio of energy per bit to noise  
 15 power spectral density used in power control to ensure that the reverse link meets the target frame error rate.

In accordance with the present invention, logic 222 is included in the MSC 210 for causing the MSC to trigger a handoff from the CDMA cell site 200 to the AMPS cell site 202 if at any given time t any one of the following  
 20 is true:

$$(1) \quad \text{FER}_{\text{forward}}(t) > \text{FER}_{\text{max\_forward}}$$

$$(2) \quad \text{FER}_{\text{reverse}}(t) > \text{FER}_{\text{max\_reverse}}$$

$$(3) \quad \text{FER}_{\text{forward}}(t) > \text{FER}_{\text{max\_forward}_2} \text{ and } \text{TCG}(t) > \text{TCG}_{\text{max}}$$

$$(4) \quad \text{FER}_{\text{reverse}}(t) > \text{FER}_{\text{max\_reverse}_2} \text{ and } \text{EBNO}(t) > \text{EBNO}_{\text{max}}$$

25 where:

**t** represents a discrete unit of time;

**FER<sub>forward</sub>(t)** is a measure of the forward frame error rate over a given window of time and is equal to:

$$5 \quad (1/N)(X_{\text{forward}}(t)) + ((N-1)/N) (\text{FER}_{\text{forward}}(t-1));$$

**FER<sub>max\_forward</sub>** is a configurable parameter for the maximum allowable FER on the forward link;

**FER<sub>reverse</sub>(t)** is a measure of the reverse frame error rate over a given window of time and is equal to:

$$10 \quad (1/N)(1/(\text{Target FER}(t-1)/\text{Target FER}(\text{fullrate}))(X_{\text{reverse}}(t)) + ((N-1)/N)(\text{FER}_{\text{reverse}}(t-1));$$

**FER<sub>max\_reverse</sub>** is a configurable parameter for the maximum allowable FER on the reverse link;

**FER<sub>max\_forward\_2</sub>** is a configurable parameter for a moderate FER on the forward link;

15 **FER<sub>max\_reverse\_2</sub>** is a configurable parameter for a moderate FER on the reverse link;

**N** is equal to averaging window size;

**X<sub>forward</sub>(t)** is equal to frame error at time t on the forward link. This is given as a percentage, with two possible values--error or no error;

20 **X<sub>reverse</sub>(t)** is equal to frame error at time t on the reverse link. This is given as a percentage with two possible values--error or no error;

**TargetFER(t)** is equal to target FER for whatever rate that the frame at time t was sent;

25 **TCG(t)** is equal to the traffic channel gain at time t on the forward link;

**TCG<sub>max</sub>** is a configurable parameter for the maximum allowable traffic channel gain;

**EBNO(t)** is equal to the **EB/NO** at time **t** on the reverse link; and  
**EBNO<sub>max</sub>** is a configurable parameter for the maximum allowable  
**EB/NO**.

It will be recognized by those skilled in the art that a calculation of  
5 **FER<sub>forward</sub>** and **FER<sub>reverse</sub>** can be easily performed using the "good frame/bad  
frame" indication as defined in "IS-95 Mobile Station-Land Station Standard  
for Dual-Mode Wideband Spread Spectrum Cellular Systems" (hereinafter  
"IS-95"), which is hereby incorporated by reference in its entirety, under  
Section 1.1.1 "Terms". Similarly, **EB** (energy per bit) is a recognized  
10 parameter defined in the above-referenced "Terms" section of IS-95. **NO**  
(noise) is the noise power spectral density and **TCG** is the power at which  
the traffic channel is broadcast.

Once any one of the above conditions (1) - (4) are met, indicating that  
the call is likely to be dropped, a CDMA-to-AMPS handoff will be initiated.  
15 In this manner, handoff of a call from the CDMA cell site 206 to the  
AMPS cell site 202 can be delayed until it is necessary to handoff the call to  
prevent the call quality from being significantly degraded or the call from  
being dropped altogether.

It will be recognized that the parameters **FER<sub>forward\_max</sub>**, **FER<sub>reverse\_max</sub>**,  
20 **FER<sub>forward\_max\_2</sub>**, **FER<sub>reverse\_max\_2</sub>**, **TCG<sub>max</sub>**, and **EBNO<sub>max</sub>** are programmable and  
can be set by a CDMA service provider according to whether the provider is  
more concerned with ensuring that calls are successfully handed off from  
CDMA to AMPS prior to the call being terminated, in which case the  
parameters would be set low, such that the call is handed off at the first  
25 indication that the quality of the call is being degraded, or with retaining the  
call on CDMA, and thus continuing to charge for the call, as long as possible,  
in which case the parameters would be set high.

Figure 3 is a flowchart of the operation of the present invention, which  
is implemented by the MSC 210 in accordance with the logic 222 stored

therein. In step 300, the current values of  $FER_{forward}$ ,  $FER_{reverse}$ , TCG and EBNO are calculated. In step 302, a determination is made whether  $FER_{forward}$  is greater than  $FER_{max\_forward}$ . If not, indicating that condition (1) above has not been met, execution proceeds to step 304, in which a  
 5 determination is made whether  $FER_{reverse}$  is greater than  $FER_{max\_reverse}$ . If not, indicating that condition (2) above has not been met, execution proceeds to step 306, in which a determination is made whether  $FER_{forward}$  is greater than  $FER_{max\_forward\_2}$ . If so, indicating that the first part of condition (3) has been met, execution proceeds to step 308, in which a determination is made  
 10 whether TCG is greater than  $TCG_{max}$ . If not, indicating that the second part of condition (3) has not been met, execution proceeds to step 310. Similarly, if in step 306, a determination is made that  $FER_{forward}$  is not greater than  $FER_{max\_forward\_2}$ , indicating that the first part of condition (3) has not been met, execution proceeds to step 310.

15 In step 310, a determination is made whether  $FER_{reverse}(t)$  is greater than  $FER_{max\_reverse\_2}$ . If so, indicating that the first part of condition (4) above has been met, execution proceeds to step 312, in which a determination is made whether  $EBNO(t)$  is greater than  $EBNO_{max}$ . If not, indicating that the second part of condition (4) above has not been met, execution returns to  
 20 step 300. Similarly, if in step 310, it is determined that  $FER_{reverse}(t)$  is less than  $FER_{max\_reverse\_2}$ , execution also returns to step 300.

If in step 312 it is determined that EBNO is greater than  $EBNO_{max}$ , indicating that both parts of condition (4) above have been met, execution proceeds to step 314, in which a hard handoff of a call from a CDMA cell  
 25 site, such as the cell site 202, to an AMPS cell site, such as the cell site 206, is triggered. Similarly, if in step 302 it is determined that  $FER_{forward}$  is greater than  $FER_{forward\_max}$ , indicating that condition (1) above has been met, or if in step 304 it is determined that  $FER_{reverse}$  is greater than  $FER_{reverse\_max}$ , indicating that condition (2) above has been met, or if in step 308 it is  
 30 determined that TCG is greater than  $TCG_{max}$ , indicating that both parts of

condition (3) above have been met, execution proceeds to step 314, in which a hard handoff of the call is triggered.

Although an illustrative embodiment of the invention has been shown and described, other modifications, changes, and substitutions are intended in the foregoing disclosure. For example, it is possible that the foregoing equations may be altered such that a handoff is triggered when a parameter is less than a predetermined minimum value, rather than greater than a predetermined maximum value and it is intended that the appended claims be construed to cover such a situation. In addition, the above-described handoff trigger of the present invention could be used to trigger handoff of a call from a first CDMA cell site to a second CDMA cell site, as well as from a CDMA cell site to an AMPS or other type of cell site on which the CDMA cell site is not overlaid. In these situations, although the way in which the call is handed off from one cell site to the other may differ, the triggering of such a handoff would be accomplished according to the teachings set forth herein. Accordingly, it is appropriate that the appended claims be construed broadly and in a manner consistent with the scope of the invention.

## WHAT IS CLAIMED IS:

- 1           1.     A method for triggering handoff of a call from a first cell site to  
2     a second cell site, the method comprising:  
3             measuring a first parameter of said call;  
4             comparing said first parameter with a predetermined value for said  
5     first parameter; and  
6             triggering a handoff of said call from said first cell site to said second  
7     cell site responsive to said first parameter deviating from said predetermined  
8     value for said first parameter at least a first predetermined amount.
- 1           2.     The method of claim 1 wherein said first parameter is selected  
2     from a group consisting of forward link erasures and reverse link erasures.
- 1           3.     The method of claim 1 further comprising:  
2             prior to said triggering, measuring a second parameter of said call;  
3     and  
4             comparing said second parameter with a predetermined value for said  
5     second parameter;  
6             wherein said triggering is performed responsive to both said first  
7     parameter deviating from said predetermined value for said first parameter  
8     at least said first predetermined amount and said second parameter  
9     deviating from said predetermined value for said second parameter at least a  
10    second predetermined amount.
- 1           4.     The method of claim 3 wherein said second parameter is  
2     selected from a group consisting of traffic channel gain and energy per bit to  
3     noise power spectral density ratio.

1           5.     The method of claim 1 wherein a first cell served by said first  
2 cell site is overlaid on a second cell served by said second cell site.

1           6.     The method of claim 1 wherein said first cell site is a CDMA  
2 cell site and said second cell site is an AMPS cell site.

1           7.     The method of claim 1 wherein said first and second cell sites  
2 are CDMA cell sites.

1           8.     A method for triggering handoff of a call from a first cell served  
2 by a first cell site to a second cell served by a second cell site, the method  
3 comprising:

4           measuring a first parameter of said call;

5           comparing said first parameter with a predetermined maximum value  
6 for said first parameter; and

7           triggering a handoff of said call from said first cell site to said second  
8 cell site responsive to said first parameter being greater than said  
9 predetermined maximum value for said first parameter.

1           9.     The method of claim 8 wherein said first parameter is selected  
2 from a group consisting of forward link erasures and reverse link erasures.

1           10.    The method of claim 8 further comprising:

2           prior to said triggering, measuring a second parameter of said call;  
3 and

4           comparing said second parameter with a predetermined maximum  
5 value for said second parameter;

6           wherein said triggering is performed responsive to both said first  
7 parameter being greater than said predetermined maximum value for said

8 first parameter and said second parameter being greater than said  
9 predetermined maximum value for said second parameter.

1 11. The method of claim 10 wherein said second parameter is  
2 selected from a group consisting of traffic channel gain and energy per bit to  
3 noise power spectral density ratio.

1 12. The method of claim 8 wherein said second cell is an AMPS cell  
2 and said first cell is a CDMA cell overlaid on said AMPS cell.

1 13. The method of claim 8 wherein said first and second cell sites  
2 are CDMA cell sites.

1 14. In a cellular communication system comprising at least one  
2 CDMA cell overlaid on an AMPS cell, a method for triggering handoff of a  
3 call from a CDMA cell site serving said CDMA cell to an AMPS cell site  
4 serving said AMPS cell, the method comprising:  
5 measuring a plurality of parameters of said call;  
6 comparing each of said parameters with a predetermined maximum  
7 value for said parameter; and  
8 triggering handoff of said call from said CDMA cell site to said AMPS  
9 cell site responsive to at least one of said plurality of parameters being  
10 greater than the predetermined maximum value therefore.

1 15. The method of claim 14 wherein said plurality of parameters  
2 comprise forward link erasures, reverse link erasures,  
3 traffic channel gain and energy-per-bit to noise power spectral density ratio.

1 16. The method of claim 14 wherein said triggering further  
2 comprises triggering handoff of said call when both said forward link

3 erasures are greater than a predetermined maximum value for said forward  
4 link erasures and said traffic channel gain is greater than a predetermined  
5 maximum value for said traffic channel gain.

1 17. The method of claim 15 wherein said triggering further  
2 comprises triggering handoff of said call when both said reverse link  
3 erasures are greater than a predetermined maximum value for said reverse  
4 link erasures and said energy-per-bit to noise power spectral density ratio is  
5 greater than a predetermined maximum value for said energy-per-bit to  
6 noise power spectral density ratio.

1 18. Apparatus for triggering handoff of a call from a first cell site to  
2 a second cell site, the apparatus comprising:  
3 means for measuring a first parameter of said call;  
4 means for comparing said first parameter with a predetermined value  
5 for said first parameter; and  
6 means for triggering a handoff of said call from said CDMA cell site to  
7 said AMPS cell site responsive to said first parameter deviating from said  
8 predetermined value for said first parameter at least a first predetermined  
9 amount.

1 19. The apparatus of claim 18 wherein said first parameter is  
2 selected from a group consisting of forward link erasures and reverse link  
3 erasures.

1 20. The apparatus of claim 18 further comprising:  
2 means for measuring a second parameter of said call; and  
3 means for comparing said second parameter with a predetermined  
4 value for said second parameter;

5            wherein said means for triggering comprises means for triggering  
6        handoff of said call responsive to both said first parameter deviating from  
7        said predetermined value for said first parameter at least said first  
8        predetermined about and said second parameter deviating from said  
9        predetermined value for said second parameter at least a second  
10       predetermined amount.

1           21.    The apparatus of claim 20 wherein said second parameter is  
2        selected from a group consisting of traffic channel gain and energy per bit to  
3        noise power spectral density ratio.

1           22.    The apparatus of claim 18 wherein said first cell site is a CDMA  
2        cell site and said second cell site is an AMPS cell site.

1           23.    The apparatus of claim 22 wherein a CDMA cell served by said  
2        CDMA cell site is overlaid on an AMPS cell served by said AMPS cell site.

1           24.    The apparatus of claim 18 wherein said first and second cell  
2        sites are both CDMA cell sites.

1           25.    A mobile switching center ("MSC") for use in a cellular system  
2        for triggering handoff of a call from a first cell site to a second cell site, the  
3        MSC comprising:  
4                logic for measuring a first parameter of said call;  
5                logic for comparing said first parameter with a predetermined value  
6        for said first parameter; and  
7                logic for triggering a handoff of said call from said CDMA cell site to  
8        said AMPS cell site responsive to said first parameter deviating from said  
9        predetermined value for said first parameter at least a first predetermined  
10       amount.

1           26.    The MSC of claim 25 wherein said first parameter is selected  
2    from a group consisting of forward link erasures and reverse link erasures.



1           27.    The MSC of claim 25 further comprising:  
2           logic for measuring a second parameter of said call; and  
3           logic for comparing said second parameter with a predetermined value  
4    for said second parameter;  
5           wherein said logic for triggering further comprises logic for triggering  
6    handoff of said call responsive to both said first parameter deviating from  
7    said predetermined value for said first parameter at least a first  
8    predetermined amount and said second parameter deviating from said  
9    predetermined value for said second parameter at least a second  
10   predetermined amount.



1           28.    The MSC of claim 27 wherein said second parameter is selected  
2    from a group consisting of traffic channel gain and energy per bit to noise  
3    power spectral density ratio.




1           29.    The MSC of claim 25 wherein said first cell site is a CDMA cell  
2    site and said second cell site is an AMPS cell site.

1           30.    The MSC of claim 29 wherein a CDMA cell served by said  
2    CDMA cell site is overlaid on an AMPS cell served by said AMPS cell site.

1           31.    The MSC of claim 25 wherein said first and second cell sites are  
2    CDMA cell sites.

*Fig. 1A**Fig. 1B*

*Fig. 1C**Fig. 1D*

*Fig. 2A**Fig. 2B**Fig. 2C*





Fig. 3



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b> <b>H04Q 7/38</b>	<b>A3</b>	<b>(11) International Publication Number:</b> <b>WO 98/27777</b> <b>(43) International Publication Date:</b> 25 June 1998 (25.06.98)
<p><b>(21) International Application Number:</b> PCT/IB97/01579</p> <p><b>(22) International Filing Date:</b> 17 December 1997 (17.12.97)</p> <p><b>(30) Priority Data:</b> 08/769,650 19 December 1996 (19.12.96) US</p> <p><b>(71) Applicant (for all designated States except US):</b> NORTHERN TELECOM LIMITED (CA/CA); World Trade Center of Montreal, 8th floor, 380 St. Antoine Street West, Montreal, Quebec H2Y 3Y4 (CA).</p> <p><b>(72) Inventors; and</b>  <b>(75) Inventors/Applicants (for US only):</b> CURTIS, David, E. [US/US]; 1550 Evergreen Drive, Allen, TX 75002 (US); BOOK, William, B. [US/US]; 1012 Winslow, Allen, TX 75002 (US); BOETTGER, David, A. [US/US]; 2111 E. Beltline Road #156A, Richardson, TX 75091 (US); JALALI, Ahmad [US/US]; 7424 Wildflower Drive, Plano, TX 75024 (US).</p> <p><b>(74) Agents:</b> MCCOMBS, David et al.; Haynes and Boone, L.L.P., Suite 3100, 901 Main Street, Dallas, TX 75202-3789 (US).</p>		<p><b>(81) Designated States:</b> AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p><b>Published</b>  <i>With international search report.</i></p> <p><b>(88) Date of publication of the international search report:</b>        8 October 1998 (08.10.98)</p>

**(54) Title:** RADIO LINK QUALITY HANDOFF TRIGGER**(57) Abstract**

A method and system is disclosed for triggering handoff of a call from a CDMA network to an AMPS network on which it is overlaid responsive to a determination that the CDMA RF link has degraded to such an extent that the call quality will be degraded significantly or the call is likely to be dropped is disclosed. A handoff of a call from a CDMA network to an AMPS network if, at a given time: (1) the number of forward link erasures is greater than a first maximum number of forward link erasures; or (2) the number of reverse link erasures is greater than a first maximum number of forward link erasures; or (3) the number of forward link erasures is greater than a second maximum number of forward link erasures and the forward traffic channel gain is greater than a maximum forward traffic channel gain; or (4) the number of reverse link erasures is greater than a second maximum number of reverse link erasures and the ratio of energy per bit to noise power spectral density on the reverse link ("EB/NO") is greater than a maximum EB/NO. In alternative embodiments, the present invention may be used to trigger handoff of a call from a first CDMA cell site to a second CDMA cell site or to an AMPS cell site serving a cell on which the cell served by the first CDMA cell site is not overlaid.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MT	Mauritius	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

# INTERNATIONAL SEARCH REPORT

In national Application No

PCT/IB 97/01579

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 6 H04Q7/38

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)  
IPC 6 H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 95 04423 A (MOTOROLA) 9 February 1995	1-3, 6, 8-10, 12, 14, 18-20, 22, 25-27, 29
A	see page 4, line 12 - page 8, line 5; figures	4, 5, 7, 11, 13, 15-17, 21, 23, 24, 28, 30, 31

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "S" document member of the same patent family

Date of the actual completion of the international search

31 July 1998

Date of mailing of the international search report

07/08/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Geoghegan, C

## INTERNATIONAL SEARCH REPORT

In ternational Application No  
PCT/IB 97/01579

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,X	US 5 649 308 A (ANDREWS) 15 July 1997  see column 3, line 22 - column 8, line 62; figures ---	1,6,8, 12-14, 18, 22-25, 29-31
P,X	US 5 640 414 A (BLAKENEY, II ET AL.) 17 June 1997	1,7,8,13
Y	see column 7, line 12 - column 27, line 60; figures ---	24,31
X	US 5 313 489 A (MENICH ET AL.) 17 May 1994	1,6,8, 12,14, 18,22, 23,25, 29,30 24,31
Y	see column 3, line 64 - column 6, line 55; figures ---	
X	EP 0 680 160 A (NTT) 2 November 1995  see page 4, column 6, line 2 - page 6, column 9, line 20; figures ---	1,3,7,8, 10,13
X	WO 90 13187 A (ERICSSON) 1 November 1990  see page 7, line 8 - page 27, line 25; figures ---	1,3,7,8, 10,13
X	WO 95 12297 A (QUALCOMM) 4 May 1995  see page 10, line 1 - page 22, line 10; figures ---	1,3,7,8, 10,13
X	WO 95 31880 A (ERICSSON) 23 November 1995 see page 4, line 28 - page 15, line 15; figures -----	1,3,8,10

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No  
PCT/IB 97/01579

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9504423 A	09-02-1995	US 5432843 A CA 2143761 A EP 0671100 A FI 951582 A	11-07-1995 09-02-1995 13-09-1995 03-04-1995
US 5649308 A	15-07-1997	NONE	
US 5640414 A	17-06-1997	US 5267261 A	30-11-1993
US 5313489 A	17-05-1994	CA 2140442 A IL 109783 A JP 8500947 T SE 9500668 A WO 9501017 A	05-01-1995 18-02-1997 30-01-1996 18-04-1995 05-01-1995
EP 680160 A	02-11-1995	JP 8018503 A CA 2147922 A CN 1115555 A	19-01-1996 28-10-1995 24-01-1996
WO 9013187 A	01-11-1990	US 5042082 A AU 625128 B AU 5530090 A CA 2030607 A KR 9513303 B US 5257401 A AU 626123 B AU 5934090 A AU 625085 B AU 5969890 A CA 2033340 A CA 2033971 A CN 1048472 A, B DE 69021794 D DE 69021794 T DE 69022307 D DE 69022307 T EP 0406186 A EP 0406193 A HK 173995 A HK 180295 A	20-08-1991 02-07-1992 16-11-1990 18-10-1990 02-11-1995 26-10-1993 23-07-1992 17-01-1991 02-07-1992 17-01-1991 27-12-1990 27-12-1990 09-01-1991 28-09-1995 22-02-1996 19-10-1995 08-02-1996 02-01-1991 02-01-1991 24-11-1995 01-12-1995

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IB 97/01579

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9013187 A		JP 4500446 T	23-01-1992
		JP 4500448 T	23-01-1992
		KR 9702756 B	10-03-1997
		KR 9709704 B	17-06-1997
		PH 26898 A	03-12-1992
		WO 9100657 A	10-01-1991
		WO 9100658 A	10-01-1991
		US 5008953 A	16-04-1991
		US 5200957 A	06-04-1993
WO 9512297 A	04-05-1995	AU 8096894 A	22-05-1995
		BR 9407896 A	19-11-1996
		CA 2173484 A	04-05-1995
		CN 1133669 A	16-10-1996
		EP 0722649 A	24-07-1996
		FI 961446 A	29-05-1996
		JP 9507115 T	15-07-1997
		ZA 9408133 A	17-05-1996
WO 9531880 A	23-11-1995	AU 688910 B	19-03-1998
		AU 2581595 A	05-12-1995
		BR 9507655 A	07-10-1997
		CA 2188755 A	23-11-1995
		CN 1148457 A	23-04-1997
		EP 0760194 A	05-03-1997
		FI 964581 A	15-11-1996
		JP 10500266 T	06-01-1998
		US 5542097 A	30-07-1996